

KillTest

质量更高 服务更好



学习资料

<http://www.killtest.cn>

半年免费更新服务

Exam : **300-425**

Title : **Designing Cisco Enterprise
Wireless Networks**

Version : **DEMO**

1.DRAG DROP

Drag and drop the characteristics from the left onto the correct functionalities on the right.

complex configuration on the Cisco WLC and infrastructure	Multiple AP-Manager Interfaces
achieves optimal AP join process with src-dst-ip load-balancing	
simple configuration on the Cisco WLC and infrastructure	LAG
avoids single point of failure on neighbor switches	

Answer:

complex configuration on the Cisco WLC and infrastructure	Multiple AP-Manager Interfaces
achieves optimal AP join process with src-dst-ip load-balancing	achieves optimal AP join process with src-dst-ip load-balancing
simple configuration on the Cisco WLC and infrastructure	simple configuration on the Cisco WLC and infrastructure
avoids single point of failure on neighbor switches	LAG
	complex configuration on the Cisco WLC and infrastructure
	avoids single point of failure on neighbor switches

2.Which UDP port numbers are used for exchange mobility packets in an AireOS wireless deployment?

- A. UDP 16666 for control plane, EoIP (IP protocol 97) for data plane
- B. UDP 16668 for control plane, UDP 16667 for data plane
- C. UDP 16667 for control plane, UDP 16666 for data plane
- D. UDP 16666 for control plane, UDP 16667 for data plane

Answer: D

3.A customer asks an engineer to explain the concept of mobility domains and mobility groups.

Which statement does the engineer respond with?

- A. A mobility group does not constrain the distribution of security context of a client and also does not constrain AP fail-over between controllers when the WLC are in the same mobility domain.
- B. If WLCs are in the same mobility domain, they communicate with each other but, if an anchor WLC is present it must be in the same mobility domain for communication to be possible.
- C. If WLCs are in the same mobility domain, they communicate with each other. Mobility groups constrain the distribution of security context of a client and also constrain AP fail-over between controllers.
- D. WLCs do not need to be in the same mobility domain to communicate with each other. Mobility groups constrain the distribution of security context of a client and also constrain AP fail-over between controllers.

Answer: C

4.An engineer is designing a wireless deployment for a university auditorium.

Which two features can be used to help deal with the issues introduced by high AP count? (Choose two.)

- A. TSPEC
- B. RXSOP
- C. TPC
- D. LSS
- E. DFS

Answer: BE

5.A wireless engineer is designing a wireless network to support real-time applications over wireless.

Which IEEE protocol must the engineer enable on the WLC so that the number of packets that are exchanged between an access point and client are reduced and fast roaming occurs?

- A. 802.11w
- B. 802.11r
- C. 802.11i
- D. 802.11k

Answer: B